

SPECIFICATIONS

No. of cylinders / valves		4L / 4
Injection System		Mechanical
Turbocharger		WG
Displacement	liters	4.5
Bore x Stroke	millimeters	104 x 132
Rated power	kW (HP) @ rpm	93 (126) @ 2200
Max Torque	Nm @ rpm	525 @ 1250
ATS		-
Certification		Stage III A / Tier 3

POWER & TORQUE

WEIGHT AND DIMENSIONS

Dimensions (L x W x H)	mm	1257 x 830 x 1075
Dry Weight	Kg	410

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS

IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

LEGEND

Air Handling

TCA (Turbocharged with aftercooler)

TC (Turbocharged)

NA (Naturally Aspirated)

Turbocharger

WG (Wastegate)

VGT (Variable Geometry Turbocharger)

TST (Twin Stage Turbocharge)

Exhaust System

EGR (Exhaust Gas Recirculation)

SCR (Selective Catalytic Reduction)

DOC (Diesel Oxidation Catalyst)

DPF (Diesel Particulate Filter)

MARINE & INDUSTRIAL
POWER

MARINE & INDUSTRIAL POWER | GENERATORS

Contact us

+64 9 299 6019

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE WWW.FPTINDUSTRIAL.COM

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE

