

SPECIFICATIONS


No. of cylinders / valves	4L / 2
Injection System	Mechanical
Turbocharger	WG
Displacement	liters 3.2
Bore x Stroke	millimeters 99 x 104
Max power	kW (HP) @ rpm 61 (82) @ 2500
Max Torque	Nm @ rpm 310 @ 1250
ATS	-
Certification	Stage III A / Tier 3

WEIGHT AND DIMENSIONS

Dimensions (L x W x H)	mm	1165 x 695 x 862
Dry Weight	Kg	300

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS

POWER & TORQUE



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

LEGEND

Air Handling

TCA (Turbocharged with aftercooler)
TC (Turbocharged)
NA (Naturally Aspirated)

Turbocharger

WG (Wastegate)
VGT (Variable Geometry Turbocharger)
TST (Twin Stage Turbocharge)

Exhaust System

EGR (Exhaust Gas Recirculation)
SCR (Selective Catalytic Reduction)
DOC (Diesel Oxidation Catalyst)
DPF (Diesel Particulate Filter)

LEESGROUP
MARINE & INDUSTRIAL POWER | GENERATORS

Contact us

+64 9 299 6019 | leesgroup.com

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE WWW.FPTINDUSTRIAL.COM
SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE