
SPECIFICATIONS

No. of cylinders / valves		4L / 4
Turbocharger		WG (TCA)
Injection System		MECHANICAL
Displacement	liters	4.5
Bore x Stroke	millimeters	104 x 132
Rated power	kW (HP) @ rpm	66 (90) @ 2200
Max Torque	Nm @ rpm	400 @ -
ATS		i-EGR
Certification		Stage III A / Tier 3

WEIGHT AND DIMENSIONS

Dimensions (L x W x H)	mm	810 x 676 x 901
Dry Weight	Kg	410

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



POWER & TORQUE



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

LEGEND

Air Handling

TC (Turbocharged)

NA (Naturally Aspirated)

TCA (Turbocharged with aftercooler)

Turbocharger

WG (Wastegate)

VGT (Variable Geometry Turbocharger)

TST (Twin Stage Turbocharge)

Exhaust System

EGR (Exhaust Gas Recirculation)

SCR (Selective Catalytic Reduction)

DPF (Diesel Particulate Filter)

DOC (Diesel Oxidation Catalyst)





+64 9 299 6019 | leesgroup com

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE WWW.FPTINDUSTRIAL.COM
SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE

