SPECIFICATIONS


No. of cylinders / valves		4L / 2
Injection System		Mechanical
Turbocharger		WG
Displacement	liters	3.2
Bore x Stroke	millimeters	99 x 104
Max power	kW (HP) @ rpm	65 (87) @ 2300
Max Torque	Nm @ rpm	350 @ 1300
ATS		-
Certification		Stage III A / Tier 3

WEIGHT AND DIMENSIONS

Dimensions (L x W x H)	mm	1165 x 695 x 862
Dry Weight	Kg	300

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS

POWER & TORQUE





IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

LEGEND

Air Handling

TCA (Turbocharged with aftercooler)

TC (Turbocharged)

NA (Naturally Aspirated)

Turbocharger

WG (Wastegate)

VGT (Variable Geometry Turbocharger)

TST (Twin Stage Turbocharge)

Exhaust System

EGR (Exhaust Gas Recirculation)

SCR (Selective Catalytic Reduction)

DOC (Diesel Oxidation Catalyst)

DPF (Diesel Particulate Filter)



Contact us

+64 9 299 6019

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE WWW.FPTINDUSTRIAL.COM SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE

