

#### SPECIFICATIONS

Certification		Tier 3
No. of cylinders		4L
Injection System		M
Air Intake		TAA
Displacement	liters	4.5
Exhaust System		I-EGR
Stand-by Power @ 1500 rpm	kWm	-
Prime Power @ 1500 rpm	kWm	-
Stand-by Power @ 1800 rpm	kWm	95
Prime Power @ 1800 rpm	kWm	87
Code		NEF45TM2X

#### WEIGHT AND DIMENSIONS

Dimensions (L x W x H)	mm	1367 x 753 x 1085
Dry Weight	Kg	500

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

#### LEGEND

##### Arrangement

L (in line)  
V (90° "V" configuration)

##### Air Handling

TCA (Turbocharged with aftercooler)  
TC (Turbocharged)  
NA (Naturally Aspirated)

##### Injection System

M (Mechanical)  
ECR (Electronic Common Rail)  
EUI (Electronic Unit Injector)  
MPI (Multi Point Injection)

**LEESGROUP**  
MARINE & INDUSTRIAL POWER | GENERATORS

Contact us

+ 64 9 299 6019 | leesgroup.com

MORE INFORMATION ABOUT CONFIGURATIONS AND ACCESSORIES AVAILABILITY, THROUGH THE WORLDWIDE FPT INDUSTRIAL DISTRIBUTORS NETWORK  
NOT ALL MODELS, STANDARD EQUIPMENT AND ACCESSORIES ARE AVAILABLE IN ALL COUNTRIES. SPECIFICATIONS AND OPTIONS MAY CHANGE WITHOUT NOTICE