


SPECIFICATIONS

Certification		Tier 3
No. of cylinders		4L
Injection System		ECR
Air Intake		TAA
Displacement	liters	4.5
Exhaust System		I-EGR
Stand-by Power @ 1500 rpm	kWm	80
Prime Power @ 1500 rpm	kWm	73
Stand-by Power @ 1800 rpm	kWm	87
Prime Power @ 1800 rpm	kWm	79
Code		NEF45TE1P

WEIGHT AND DIMENSIONS

Dimensions (L x W x H)	mm	1367 x 753 x 1086
Dry Weight	Kg	450

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

LEGEND

Arrangement

L (in line)
V (90° "V" configuration)

Air Handling

TCA (Turbocharged with aftercooler)
TC (Turbocharged)
NA (Naturally Aspirated)

Injection System

M (Mechanical)
ECR (Electronic Common Rail)
EUI (Electronic Unit Injector)
MPI (Multi Point Injection)

LEESGROUP
MARINE & INDUSTRIAL POWER | GENERATORS

Contact us

+ 64 9 299 6019 | leesgroup.com

MORE INFORMATION ABOUT CONFIGURATIONS AND ACCESSORIES AVAILABILITY, THROUGH THE WORLDWIDE FPT INDUSTRIAL DISTRIBUTORS NETWORK
NOT ALL MODELS, STANDARD EQUIPMENT AND ACCESSORIES ARE AVAILABLE IN ALL COUNTRIES. SPECIFICATIONS AND OPTIONS MAY CHANGE WITHOUT NOTICE