

INDUSTRIAL

Power Units

N45

N45
93 kW (126 HP) @ 2200 rpm
Stage III A / Tier 3

SPECIFICATIONS

No. of cylinders / valves	4L / 4
Injection System	Mechanical
Turbocharger	WG
Displacement	liters 4.5
Bore x Stroke	millimeters 104 x 132
Rated power	kW (HP) @ rpm 93 (126) @ 2200
Max Torque	Nm @ rpm 525 @ 1250
ATS	-
Certification	Stage III A / Tier 3

POWER & TORQUE

WEIGHT AND DIMENSIONS

Dimensions (L x W x H)	mm	1257 x 830 x 1075
Dry Weight	Kg	410

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

POWER UNITS

LEGEND

Air Handling

TCA (Turbocharged with aftercooler)
TC (Turbocharged)
NA (Naturally Aspirated)

Turbocharger

WG (Wastegate)
VGT (Variable Geometry Turbocharger)
TST (Twin Stage Turbocharge)

Exhaust System

EGR (Exhaust Gas Recirculation)
SCR (Selective Catalytic Reduction)
DOC (Diesel Oxidation Catalyst)
DPF (Diesel Particulate Filter)

MARINE & INDUSTRIAL
POWER

MARINE & INDUSTRIAL POWER | GENERATORS

Contact us

+ 64 9 299 6019

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE WWW.FPTINDUSTRIAL.COM
SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE